


# COTS Commercial Grade 3U Rackmount Computer System

## C346 Photos



I/O connectors are dependent upon the model selected. See specifications for details.

## Who We Are

### CHASSIS PLANS

- Chassis Plans designs, fabricates and integrates standard and customized high-performance computing platforms and LCD monitors for military, industry, and commercial applications.
- Using COTS components, Chassis Plans provides solutions for customers who need reliable systems that will operate in a variety of harsh conditions and who require revision control and hardware consistency for multi-year programs.
- Chassis Plans is an ITAR Registered and SBA-certified small business that has been operating in Southern California for over a decade.

### YOUR CONFIGURATION. ONE PART NUMBER.

- It's our mission to make your life easier. Our Sales Engineers will help you select the right configuration for your project, making sure the details are analyzed and that the system meets your specifications.
- One part number means easier procurement and less paperwork for you.
- Dedicated Sales and Program Managers.
- Last time buy opportunities for end-of-life components.



Models C34601, C34607, C34608, C34609, C34613

Assembled in the USA  
ISO 9001:2008 Certified  
ITAR Registered

Our C346 computing platform can be used for many computationally-intensive applications, while occupying only 3RU. With the added security of sturdy construction, this system has revision controlled, long-life components that provide stability for long program duration.

Specifications for our standard products can always be customized to fit your unique application requirements.

In-house Engineering Department

Rapid Prototyping

### CPU Options

- Single Intel® Core i5® or i7®
- Single Intel® Xeon® E3 Series
- Single or Dual Intel® Xeon® E5 Series

### Drive Capacity

- 6(x) 5.25" External Drive Bay
- 1(x) 3.5" External Drive Bay
- 2(x) 3.5" Internal Drive Bay

### Applications

- Aviation
- Broadcast
- Energy
- Telemetry
- Diagnostics
- Simulation
- C4ISR
- Communications
- Imaging
- Persistent Surveillance
- Public Safety
- Automation
- Test and Measurement
- Transportation
- Medical



### Benefits

- Revision-Controlled Components
- Long-Life Components
- Optimal for Long Program Life Cycles
- Excellent Value over Program Life
- Variety of Expansion Slots Available

### Environments


Components meet the below specifications.

#### HIGH TEMPERATURE

50°C Operational, 85°C Storage  
C34609: 35° Operational, 70°C Storage

#### LOW TEMPERATURE

0°C Operational, -20°C Storage  
C34609: 0°C Operational, -40°C Storage



For more information visit  
[www.chassis-plans.com](http://www.chassis-plans.com)  
or call 858.571.4330

Chassis Plans  
10840 Thornmint Road · San Diego, CA 92127

©2016 Chassis Plans LLC. All Rights Reserved. No part of this document may be copied or reproduced without prior consent.

C346-1216

For more information visit  
[www.chassis-plans.com](http://www.chassis-plans.com)  
or call 858.571.4330



# COTS Commercial Grade 3U Rackmount Computer System

MILITARY | INDUSTRIAL | COMMERCIAL



## Chassis Specifications

### DIMENSIONS

19" X 5.25" X 25.6" (482.6mm X 133.6mm X 650.2mm)

### WEIGHT

47 pounds, weight varies by configuration

### ENCLOSURE FEATURES

#### Construction

Heavy duty, cold-rolled electroplated steel

#### Front Door

Single door with 2(x) thumb screws

#### Drive Capacity

6(x) 5.25" internal drive bay  
1(x) 3.5" external drive bay  
2(x) 3.5" internal drive bay

#### Indicators

Power on, hard drive access

#### Switches

System power, system reset switches

### FRONT USB PORTS

(2x) ports USB 2.0

### SYSTEM COOLING


(4x) 92mm cooling fans

### MOTHER BOARD CAPACITY

Designed for ATX-sized motherboard (13" X 12")

### POWER SUPPLY

Single or redundant 600W 110/220 Volt AC  
Other power options available



## Computer Specifications

	C34601	C34607	C34608	C34609	C34613
<b>CPU</b>	Single Intel® Core i7®-860, 2.80GHz OR Single Intel® Core i5®-660, 3.33GHz	Single Intel® Core™ i7-3770 (8M Cache, up to 3.9GHz), Intel® Core™ i5-3550S (6M Cache, up to 3.7GHz), Single Intel® Core™ i7-2600 Processor (8M Cache, 3.4GHz) OR Single Intel® Core™ i5-2400 Processor (6M Cache, 3.1GHz)	Single Intel® Xeon® Processor E3-1275 (8M Cache, 3.4GHz) OR Single Intel® Xeon® Processor E3-1225 (6M Cache, 3.1GHz)	Single or Dual Intel® Xeon® Processor E5-2658 (20M, 2.10GHz, 8.0 GT/s Intel® QPI) OR Single or Dual Intel® Xeon® Processor E5-2428L (15M, 1.80GHz, 7.2 GT/s Intel® QPI)	Single Intel® Core i7-4770S 3.9GHz OR Single Intel® Core i5-4570S 3.6GHz
<b>CHIP SET</b>	Intel® Q57 Platform Controller Hub (PCH)	Intel® Q67 Platform Controller Hub (PCH)	Intel® C216 Platform Controller Hub (PCH)	Intel® C606 Platform Controller Hub (PCH)	Intel® Q87 Express
<b>MAX RAM</b>	(4x) 240-pin DDR3 Max. 16GB	(4x) 240-pin DDR3 Max. 32GB	(4x) 240-pin DDR3 Max. 32GB	(8x) 240-pin DDR3 Max. 256GB ECC	(4x) 240-pin DDR3 Max. 32GB
<b>HARD DRIVES</b>	Up to (4x) SATA2, 500GB, 7200 RPM, 64GB cache standard. In fixed or removable configurations.	Up to (4x) SATA2, 500GB, 7200 RPM, 64GB cache standard. In fixed or removable configurations.	Up to (4x) SATA2, 500GB, 7200 RPM, 64GB cache standard. In fixed or removable configurations.	Up to (4x) SATA2, 500GB, 7200 RPM, 64GB cache standard. In fixed or removable configurations.	Up to (4x) SATA2, 500GB, 7200 RPM, 64GB cache standard. In fixed or removable configurations.
<b>RAID OPTION</b>	JBOD, RAID 0, 1, 5	JBOD, RAID 0, 1, 5	JBOD, RAID 0, 1, 5	JBOD, RAID 0, 1, 5	JBOD, RAID 0, 1, 5
<b>OPTICAL DRIVE</b>	24x DVDRW	24x DVDRW	24x DVDRW	24x DVDRW	24x DVDRW
<b>EXPANSION SLOTS</b>	(1x) PCIe x16 (GEN 2.0), (1x) PCIe x4 (GEN 1.0), (2x) PCIe x1 (GEN 1.0) & (3x) PCI (PCI 2.3)	(1x) PCIe x16 (GEN 3.0), (1x) PCIe x4 (GEN 2.0), (1x) PCIe x1 (GEN 2.0) & (4x) PCI (PCI 2.3)	(2x) PCIe x16 (GEN 3.0), (2x) PCIe x4 (GEN 2.0), (1x) Mini PCIe (GEN 2.0) & (3x) PCI (PCI 2.3)	(3x) PCIe x8 (GEN 3.0), (1x) PCIe x4 (GEN 2.0), (1x) PCIe x1 (GEN 2.0), (1x) PCI (PCI 2.3)	(1x) PCIe x16 (GEN 3.0), (1x) PCIe x4 (GEN 2.0) (1x) x1 (GEN 2.0) (3x) PCI (PCI 2.3)
<b>REAR I/O</b>	(2x) PS/2 ports, (2x) DB-9 RS232 serial ports, (1x) DVI-I port (DVI-D signal only), (1x) DB-15 VGA port, (2x) RJ45 LAN ports, (4x) USB 2.0/1.1 ports, (1x) Mic-in, (1x) line-in and (1x) line out	(1x) mini-DIN-6 port for PS/2 mouse/keyboard, (2x) DB-9 RS232 serial ports, (1x) DVI-I port (DVI-D signal only), (1x) DB-15 VGA port, (2x) RJ45 LAN ports, (6x) USB 2.0/1.1 ports, (1x) Mic-in, (1x) line-in and (1x) line out	(1x) mini-DIN-6 port for PS/2 mouse/keyboard, (1x) DB-9 RS232 serial port, (2x) DVI-I ports (DVI-D signal only) & (1x) HDMI port, (2x) RJ45 LAN ports, (4x) USB 3.0 ports, (2x) USB 2.0 ports, (1x) Mic-in, (1x) line-in and (1x) line out	(1x) DB-9 RS232 serial port, (2x) RJ45 GbE LAN ports, (4x) USB 2.0 ports, (1x) RJ45 dedicated IPMI, DB-15 VGA port, (1x) UID switch	(1x) PS/2 ports, (2x) DB-9 RS232 serial ports, (1x) DVI-I port (DVI-D signal only), (1x) HDMI Port, (2x) RJ45 LAN ports, (4x) USB 3.0 ports (2x) USB 2.0 ports, (1x) Mic-in, (1x) line-in and (1x) line out
<b>ON BOARD GRAPHICS</b>	Intel® HD Graphics	Intel® HD Graphics	Intel® HD Graphics 4000P	Matrox G200eW	Integrated Intel® HD Graphics DVI-I Out (DVI-D only) HDMI
<b>AUDIO</b>	Realtek® ALC262 Stereo ADCs and S/PDIF Interface	Realtek® ALC886 5.1-channel High Definition Audio	Realtek® ALC886 5.1-channel High Definition Audio	N/A	Realtek® ALC886 5.1 High Definition Audio
<b>LAN</b>	(1x) Realtek® RTL8111DL PCI Express Gigabit Ethernet controller and (1x) Intel® W82578DM with iAMT6.0 Gigabit Ethernet PHY	(1x) Intel® WG82579LM with iAMT7.0 Gigabit Ethernet Phy & (1x) Intel® WG82574L PCI Express Gigabit Ethernet controller	(1x) Intel® WG82579LM with iAMT8.0 Gigabit Ethernet Phy & (1x) Intel® WG82574L PCI Express Gigabit Ethernet controller	(2x) Intel® 82574L Gigabit Ethernet controllers, (1x) Realtek® RTL8201N PHY dedicated IPMI	Intel I210 PCI Express Gigabit Ethernet controller, Intel I217LM with iAMT9.0 Gigabit Ethernet Phy
<b>O/S</b>	Windows XP® Pro, Windows 7® Pro, 32 & 64-bit Other O/S Available	Windows XP® Pro, Windows 7® Pro, 32 & 64-bit Other O/S Available	Windows XP® Pro, Windows 7® Pro, 32 & 64-bit Other O/S Available	Windows XP® Pro, Windows 7® Pro, 32 & 64-bit Other O/S Available	Windows XP® Pro, Windows 7® Pro, 32 & 64-bit Other O/S Available