# COTS Rugged Industrial Grade 5U Rackmount Computer System



Models R5U2210, R5U2211

Assembled in the USA ISO 9001:2008 Certified ITAR Registered

Our rugged R5U-22 can be used for many in-field data-intensive applications such as persistent surveillance, simulation, and radar processing applications. With the correct configuration, the R5U-22 can also serve as a GPU Server. It contains our proprietary SysCool® thermal management system, which extends the life of the computing system, reduces power consumption, and lowers overall system noise levels.

Specifications for our standard products can always be customized to fit your unique application requirements.

In-house Engineering Department

Rapid Prototyping

# **CPU & Memory Options**

- Single or Dual Intel® Xeon® E5 Series
  - ° CPU options up to 2.1GHz, 8 Cores
  - Memory options up to 512GB

# **Drive Capacity**

- 4(x) 3.5" Drive Bays
- 1(x) Slim Slot-Fed Optical Drive

# **Applications**

- Airborne Operations
- Land-based Operations
- Seaborne Operations
- Telemetry
- · Diagnostics
- Simulation
- Communications
- · Imaging
- Persistent Surveillance
- UAVs
- Automation
- Severe Environment Operations



## **Harsh Environments**

Designed to meet or exceed the below environmental specifications.

#### **ALTITUDE**

12,000 ft Operational, 40,000 ft Storage

#### **HIGH TEMPERATURE**

50°C Operational, 70°C Storage

#### **LOW TEMPERATURE**

0°C Operational, -20°C Storage

#### **HUMIDITY**

5-95%, Non-condensing

#### **VIBRATION**

2G RMS 5-500Hz

## BENCH HANDLING SHOCK DROP TEST

20G @ 11ms Duration

# **COTS Rugged Industrial Grade 5U Rackmount Computer System**

# MILITARY | INDUSTRIAL | COMMERCIAL

# **Chassis Specifications**

#### **DIMENSIONS**

19" X 8.75" X 22" (482.6mm X 222.3mm X 558.8mm)

#### **WEIGHT**

62 pounds, weight varies by configuration

#### **ENCLOSURE FEATURES**

#### Construction

Front Panel: 0.235" milled 5052-H32 aircraft-grade aluminum Enclosure Body: 0.093" 5052-H32 aircraft-grade aluminum Rear Slot Panel: 16 gauge CRS, zinc plated with 10-32 grounding lug

#### Front Door

Aluminum, formed and welded, with three captive closure fasteners Milled channel with environmental gasket Built in, removable, washable air filter

#### **Drive Capacity**

4(x) 3.5" drive bays

1(x) slim slot-fed optical drive

#### **Indicators**

Power on, disk access, fan failure and over temperature indicators

#### Switches

Power and alarm reset switches behind front door

#### Powdercoating

Black per MIL-PRF-24712, Type IV, Class 3, Cardinal C214-BK110 polyester semi-gloss, fine texture

#### Plating

Chem-Film per MIL-C-5541F, Class 1A

#### FRONT USB PORTS

(2x) ports USB 2.0

#### SYSTEM COOLING

(3x) 120mm, 150 CFM, 200K hour MTBF cooling fans Proprietary SysCool<sup>TM</sup> intelligent adaptive fan controller and temperature alarm circuit board

#### **MOTHER BOARD CAPACITY**

Designed for motherboards up to 15" x 13"

#### **POWER SUPPLY**

Redundant 1500W 110/220 Volt AC Other power options available

#### **LCD Power Alternative**

Chassis Plans' 2U-5U rackmount computer systems are designed with a removable back plate that allows a 12V power cord to run from the computer's power supply to a display or keyboard video monitor. This optional feature, the Exterior Power Jack, is available for most Chassis Plans' monitors.

By running the display with the computer systems' power supply, this Exterior Power Jack option can provide many benefits:

- Reduction in the number of required cables
- Elimination of additional equipment, i.e., a power brick
- · Reduction in total system weight and cost

To enjoy these benefits, power up your new display with this Chassis Plans' server.

#### **R5U-22A Photos**

19"





I/O connectors are dependent upon the model selected. See specifications for details.

8.75



# **Computer Specifications**

|                   | R5U2210   | R5U2211   |
|-------------------|---|---|
| CPU               | Single or Dual Intel® Xeon® Processor<br>E5-2658 (20M, 2.10 GHz, 8.0 GT/s<br>Intel® QPI)<br>OR<br>Single or Dual Intel® Xeon® Processor<br>E5-2428L (15M, 1.80 GHz, 7.2 GT/s<br>Intel® QPI) | Single or Dual Intel <sup>®</sup> Xeon <sup>®</sup> Processor<br>E5-2658 (20M, 2.10 GHz, 8.0 GT/s<br>Intel <sup>®</sup> QPI)<br>OR<br>Single or Dual Intel <sup>®</sup> Xeon <sup>®</sup> Processor<br>E5-2428L (15M, 1.80 GHz, 7.2 GT/s<br>Intel <sup>®</sup> QPI) |
| CHIP SET          | Intel® C600-A Platform Controller<br>Hub (PCH), QPI up to 8.0 GT/s  | Intel® C602 Platform Controller Hub<br>(PCH), QPI up to 8.0 GT/s  |
| /MAX RAM          | (16x) 240-pin DDR3, Max. 512GB<br>DDR3 ECC Reg.   | (16x) 240-pin DDR3, Max. 512GB<br>DDR3 ECC Reg.   |
| HARD DRIVES       | Up to (4x) 2.5" SATA2, 500GB, 7200 RPM, 64GB cache standard. In fixed or removable configurations. Other rotating media and solid state storage sizes available                             | Up to (4x) 2.5" SATA2, 500GB, 7200 RPM, 64GB cache standard. In fixed or removable configurations. Other rotating media and solid state storage sizes available   |
| RAID OPTION       | JBOD, RAID 0, 1, 5  | JBOD, RAID 0, 1, 5  |
| OPTICAL DRIVE     | Slim Slot-Fed 8x DVDRW  | Slim Slot-Fed 8x DVDRW  |
| EXPANSION SLOTS   | (4x) PCIe x16 (Gen 3.0), (1x) PCIe x8<br>(Gen 3.0), (1x) PCIe x4 (Gen 2.0)  | (10x) PCIe x8 (Gen 3.0), (1x) PCIe x4<br>(Gen 2.0)  |
| REAR I/O          | (1x) DB-9 RS232 serial port, (4x) RJ45<br>GbE LAN ports, (4x) USB 2.0 ports,<br>(1x) DB-15 VGA port   | (1x) DB-9 RS232 serial port, (2x) RJ45<br>GbE LAN ports, (4x) USB 2.0 ports,<br>(1x) RJ45 dedicated IPMI, DB-15<br>VGA port, (1x) UID switch  |
| ON BOARD GRAPHICS | Matrox G200   | Matrox G200eW   |
| AUDIO             | NA  | NA  |
| /LAN              | (4x) Gigabit through Intel® i350-AM<br>Quad 10/100/1000 integrated GbE<br>MAC and PHY controller  | Dual Intel® i350 Gigabit ethernet ports<br>& (1x) Realtek® RTL8201N PHY<br>(dedicated IPMI)   |
| / o/s             | Windows XP® Pro, Windows 7® Pro,<br>32 & 64-bit<br>Other O/S Available  | Windows XP® Pro, Windows 7® Pro,<br>32 & 64-bit<br>Other O/S Available  |



### Who We Are

#### **CHASSIS PLANS**

- Chassis Plans designs, fabricates and integrates standard and customized high-performance computing platforms and LCD monitors for military, industry, and commercial applications.
- Using COTS components, Chassis Plans provides solutions for customers who need reliable systems that will operate in a variety of harsh conditions and who require revision control and hardware consistency for multi-year programs.
- Chassis Plans is an ITAR Registered and SBA-certified small business that has been operating in Southern California for over a decade.

#### **ENGINEERED TO YOUR SPECIFICATIONS**

- In-house engineering department
- Design and build of rapid prototypes. Experience with solving difficult customer application problems through knowledge of the industry and custom system design and manufacturing capability
- Our Engineers use Solid Works 3D CAD modeling software for mechanical design and thermal simulation
- Design experience with MIL-STD-167, MIL-STD-461, MIL-STD-810, and MIL-S-901, in addition to FCC, UL, CE, and country specific agency requirements

#### YOUR CONFIGURATION. ONE PART NUMBER.

- It's our mission to make your life easier. Our Sales Engineers
  will help you select the right configuration for your project,
  making sure the details are analyzed and that the system
  meets your specifications.
- One part number means easier procurement and less paperwork for you.
- · Dedicated Sales and Program Managers.
- · Last time buy opportunities for end-of-life components.

#### **FACILITY AND TEST**

- All integration work is performed in a state-of-the-art, ESD-controlled facility
- Our facility has 23,000 sqft and has dedicated 12,000 sqft to manufacturing and 3,000 sqft to engineering
- Operate to anti-static standard ANSI/ESD S20.20-2007 and electronics assembly standard IPC-A-610, Revision E-2010

#### **QUALITY COUNTS**

- ISO 9001:2008 Certified
- 100% system inspection before shipment
- All integrated systems undergo a minimum 24-hour system test and burn-in before shipment to the customer
- Assistance with 3rd party verification of system specifications
- 2-year warranty on all integrated systems and LCD monitor products
- · Assembled in the USA

