



CKX

RUGGED RACKMOUNT KEYBOARD



RUGGED 1U KEYBOARD

Our CKX Keyboard can be used for many rugged military applications. You have the option of a trackball or touch pad. The keyboard has exceptional strength, is low weight, and works well under extreme temperature swings. The drawer includes friction slides for mounting into a 19" rack. The drawer uses screw locks to secure it into the rack for transportation.

Its compact size and light weight rugged construction make it ideal for use in all manner of adverse conditions. The use of friction slides versus ball bearing slides allows it to be used in vehicular and mobile missions such as in the back of a moving Humvee.

BUILT TO TAKE ON THE HARSHTEST ENVIRONMENTS

CP North America designs, builds, and tests our ruggedized offerings to meet MIL-STD-810, 461, and 901. This includes environmental factors such as:

- HIGH ALTITUDE
- EXTREME HIGH & LOW TEMPERATURES
- EMI
- HUMIDITY
- BLOWING SAND AND DUST
- VIBRATION
- SHOCK

Who We Are

CP North America designs, fabricates, and integrates standard and customized high-performance computing platforms and LCD monitors for military, industrial, and commercial applications.

Using COTS components, CP North America provides solutions for customers who need reliable systems that will operate in a variety of harsh conditions and who require revision control and hardware consistency for multi-year programs.

CP North America is an ITAR Registered and ISO 9001:2015 Certified business that has been operating for over twenty years.

Assembled in the USA
ISO 9001:2015 Certified
ITAR Registered

CP North America
2620 Deep Well Ranch Rd
Prescott, AZ 86301
cpna.tech
928.239.9500



TECH SPECS

DIMENSIONS	19" X 1.75" X 16" (482.6mm X 44.45mm X 404.4mm) Fits racks from 16" to 30" of depth with appropriate slide brackets Minimum keyboard extension: 9.3" (to clear rear of keyboard) Full keyboard extension: 15.5" (to lock engagement)
SHIPPING WEIGHT	11 lbs typical, varies by configuration
REAR PANEL	Includes cable management arm Cable Length: Approximately 36" (from rear of cable management arm) PS/2 Model: 2 PS/2 connectors for trackball and keyboard USB Model: 1 USB connector (trackball and keyboard signals on same connector)
PLATING	Chem-Film per MIL-C-5541F, Class 1A
POWDERCOATING	Black per MIL-PRF-24712, Type IV, Class 3, Cardinal C214-BK110 polyester semi-gloss, fine texture
SLIDES	Solid Bearing Slides (Friction Slides), 15.4-inches of travel Lock-out button. Stainless self-locking hardware throughout Includes Extension Bracket (0 to 6.5" extension) Includes Extension Bracket (3 to 11" extension)
KEYBOARD SPECS	Sealed silicon keys with Dura-coating NEMA4 (IP65) rated PS/2 or USB connection High-quality carbon-on-gold switch elements Tactile keystroke 10,000,000 lifecycles per switch Synchronous 8-bit data
TRACKBALL SPECS	Separate from keyboard assembly 38mm ball Sealed to NEMA4 (IP65 static, IP54 dynamic) standards, water and dust proof from front surface Two mouse buttons >6 million revolutions lifetime
TOUCHPAD SPECS	Keyswitch Technology: Gold Plated Domes Protection Level: IP65 (Front) Operating Force: 3.0N Operating Principle: Capacitive Resolution: 100-300dpi Active Area: 59x42mm

QUESTIONS?

Reach out to us at
cpna.tech
or call 928.239.9500

ENGINEERED TO YOUR SPECIFICATIONS

- In-house engineering department
- Design and build of rapid prototypes. Experience with solving difficult customer application problems through knowledge of the industry and custom system design and manufacturing capability
- Our Engineers use Solid Works 3D CAD modeling software for mechanical design and thermal simulation
- Design experience with MIL-STD-167, MIL-STD-461, MIL-STD-810, and MIL-S-901, in addition to FCC, UL, CE, and country specific agency requirements

REVISION CONTROL & CONFIGURATION MANAGEMENT

- Our Program Managers will assure your products are revision controlled for the life of the program
- Configuration Management to assure TAA Compliance and system compatibility
- One part number for life of the program
- Counterfeit and obsolescence management

FACILITY AND TEST

- All integration work is performed in a state-of-the-art, ESD-controlled facility
- Our facility has 50,000 sqft and has dedicated areas for manufacturing and engineering
- Operate to anti-static standard ANSI/ESD S20.20-2007 and electronics assembly standard IPC-A-610, Revision E-2010

QUALITY COUNTS

- ISO 9001:2015 Certified
- 100% system inspection before shipment
- All integrated systems undergo a rigorous system test and burn-in before shipment to the customer
- 5-year warranty on all servers and 3-year warranty on LCD monitor products
- TAA compliant
- Built in the USA

CP North America
2620 Deep Well Ranch Rd
Prescott, AZ 86301