



M2U | 2U HIGH PERFORMANCE COMPUTER

2U COMPUTER

The M2U high-performance computing platform delivers rugged durability in a standard 2U rackmount form factor. Like most CP North America products, the M2U is built using industry standard COTS componentry and can be customized to meet the performance needs of each and every customer.

Featuring support for standard ATX size motherboards, the M2U is capable of mounting up to 12x 2.5" removeable drives and an array of PCI and/or PCI Express expansion cards.

Utilizing our proprietary SysCool® thermal management system and built to the highest of MIL-grade standards, the M2U is designed to meet modern high-performance computing demands while delivering consistent and reliable performance in the harshest of rackmount environments. Additionally, this is backed by our standard 5-year warranty, revision control and configuration management to ensure that current and future hardware remain supported throughout the life of any program it may be deployed in.



APPLICATIONS

- Airborne Operations
- Land-based Operations
- Seaborne Operations
- Telemetry
- Diagnostics
- Simulation
- C4ISR
- Communications
- Imaging
- Persistent Surveillance
- UAVs
- Automation
- Severe Environment Operations

Who We Are

CP North America designs, fabricates, and integrates standard and customized high-performance computing platforms and LCD monitors for military, industrial, and commercial applications.

Using COTS components, CP North America provides solutions for customers who need reliable systems that will operate in a variety of harsh conditions and who require revision control and hardware consistency for multi-year programs.

CP North America is an ITAR Registered and ISO 9001:2015 Certified business that has been operating for over twenty years.

Assembled in the USA
ISO 9001:2015 Certified
ITAR Registered

CP North America
2620 Deep Well Ranch Road
Prescott, AZ 86301
cpna.tech
928.239.9500



TECH SPECS

COMPUTER SPECIFICATIONS

CPU OPTIONS	Single or Dual Intel Core or Xeon Processors
MEMORY CAPACITY	ECC or Non-ECC Modules, varies with configuration
RAID OPTION	JBOD, RAID 0, 1, 5
MOTHERBOARD	ATX Form Factor
PCI-E EXPANSION	Up to (3x) Vertically or (7x) Horizontally mounted card slots
REAR I/O	Varies with configuration
LAN	Varies with configuration
FRONT USB PORTS	(2x) ports USB
SYSTEM COOLING	(5x) 40mm, 18.4 CFM, 100K hour MTBF cooling fans Proprietary SysCool™ intelligent adaptive fan controller and temperature alarm circuit board
POWER SUPPLY	Available in 110-240VAC, 12VDC, 28VDC, 48VDC

EXPANSION CAPACITY

- (4x) 2.5" Drive Bays, Shock-Isolated
Expandable up to 12x drive bays
- 1(x) Slim Slot-Fed Optical Drive
- 1(x) Flash Card Reader Bay (optional)
- Additional M.2 drives, varies by motherboard configuration

FRONT DOOR FEATURES

Milled aluminum with four captive closure fasteners
 Milled channel with RF/EMI/environmental gasket
 Attenuating EMI honeycomb filter with 45 PPI (washable) air filter rated to UL 94 HF-1



TECH SPECS


CHASSIS SPECIFICATIONS

DIMENSIONS	19" X 3.5" X 20" (482.6mm X 88.9mm X 508mm)
WEIGHT	28 lbs (approximate weight. Varies with configuration)
CONSTRUCTION	Front Panel: 0.250" milled 5052-H32 aircraft-grade aluminum Enclosure Body: 0.090" 5052-H32 aircraft-grade aluminum Rear Slot Panel: 18 gauge CRS, zinc plated with 10-32 grounding lug
POWDERCOATING	Black per MIL-PRF-24712, Type IV, Class 3, Cardinal C214-BK110 polyester semi-gloss, fine texture
PLATING	Chem-Film per MIL-C-5541F, Class 1A

HARSH ENVIRONMENTS

CP North America designs, builds, and tests our ruggedized offerings to meet MIL-STD-810, 461, and 901. This includes environmental factors such as:

- **HIGH ALTITUDE**
- **EXTREME HIGH & LOW TEMPERATURES**
- **EMI**
- **HUMIDITY**
- **BLOWING SAND AND DUST**
- **VIBRATION**
- **SHOCK**



ENGINEERED TO YOUR SPECIFICATIONS

- In-house engineering department
- Design and build of rapid prototypes. Experience with solving difficult customer application problems through knowledge of the industry and custom system design and manufacturing capability
- Our Engineers use Solid Works 3D CAD modeling software for mechanical design and thermal simulation
- Design experience with MIL-STD-167, MIL-STD-461, MIL-STD-810, and MIL-S-901, in addition to FCC, UL, CE, and country specific agency requirements

REVISION CONTROL & CONFIGURATION MANAGEMENT

- Our Program Managers will assure your products are revision controlled for the life of the program
- Configuration Management to assure TAA Compliance and system compatibility
- One part number for life of the program
- Counterfeit and obsolescence management

FACILITY AND TEST

- All integration work is performed in a state-of-the-art, ESD-controlled facility
- Our facility has 50,000 sqft and has dedicated areas for manufacturing and engineering
- Operate to anti-static standard ANSI/ESD S20.20-2007 and electronics assembly standard IPC-A-610, Revision E-2010

QUALITY COUNTS

- ISO 9001:2015 Certified
- 100% system inspection before shipment
- All integrated systems undergo a rigorous system test and burn-in before shipment to the customer
- 5-year warranty on all servers and 3-year warranty on LCD monitor products
- TAA compliant
- Built in the USA

CP North America
2620 Deep Well Ranch Rd
Prescott, AZ 86301